

Department of Consumer and Business Services Oregon Occupational Safety & Health Division (OR-OSHA) 350 Winter Street NE, Room 430 P.O. Box 14480 Salem, OR 97309-0405 Phone: (503) 378-3272 Toll Free: 1-800-922-2689 Fax: (503) 947-7461 www.orosha.org

December 19, 1991

Mr. Dennis Pruitt Weyerhaeuser Lumber Co. PO Box 667 Cottage Grove, OR 97424

Dear Mr. Pruitt:

This is in response to your phone request for assistance regarding the securing of loads of lumber on trucks as they move from your loading area to your scales prior to departing your yard.

After my visit to your facility and a review of OAR 437-002-1910.265, our Technical Manager and Enforcement manager reviewed my observations and your concerns.

OAR 437-002-1910.265(c)(28), "Loads shall be built and secured to assure stability in transit." The key words are "and secured" which clearly requires that the load be tied down in accordance with other provisions of the code which describe the proper methods. Also at issue was the definition of the words, "in transit." OR-OSHA would include the trip between your **loading area** and scales as within the meaning of "in transit."

In summary, you need to take measures to assure that drivers are moving to your tiedown area and are in fact securing their loads before they make the trip to the scales.

If we can be of further assistance, please contact us.

Sincerely,

Ron Preece Safety Specialist Standards and Technical Resources Oregon Occupational Safety and Health Division (503) 378-3272

6/22/04 this interpretation was updated to reflect the appropriate rule numbers.